光华化工
GUANGHUA CHEMICAL

化学品安全技术说明书（SDS）

产品：**热镀锌消泡剂（ZY- 9174）**

编制依据：**GB/T 16483- 2008、GB/T 17519- 2013、GB 30000 系列 GHS 分类标准**

1 化学品及企业标识

1.1 商品名称：热镀锌消泡剂（ZY- 9174）

1.2 别名：有机硅聚醚改性乳液型抑泡消泡剂

1.3 产品推荐用途：本品为水溶性高效抑泡消泡剂，兼具快速消泡与长效抑泡双重功能；可在高温、强酸碱、高剪切力工况稳定使用；适用于工业清洗液、涂料、胶粘剂、热镀锌相关水处理体系；可原液直接投加或稀释后使用，推荐添加量 0.1%- 0.3%，使用前适度搅拌。

1.4 禁止用途：不得用于食品、医药、饮用水体系。

1.5 生产企业：昆山光华化工材料有限公司

1.6 企业地址：江苏省昆山市巴城镇湖滨北路 341 号

1.7 联系电话：13584927325

1.8 24 小时国内应急咨询电话：13584927325

1.9 编制部门：技术工程部

1.10 编制日期：2026- 08- 20

1.11 修订版本：V2.0

2 危险性概述

2.1 GHS 危险性分类：皮肤刺激（类别 2）；眼刺激（类别 2A）；对水生生物有害并具有长期持续影响；不燃液体，无爆炸危险。

2.2 GHS 象形图：感叹号 ⚠ GHS07

2.3 信号词：警告

2.4 危险说明： H315：造成皮肤刺激； H319：造成严重眼刺激； H412：对水生生物有害并具有长期持续影响。

2.5 防范说明： P280：戴防护手套、防护眼镜； P302+P352：如皮肤接触，用大量肥皂水清水冲洗； P305+P351+P338：如入眼睛，清水持续冲洗数分钟，取出隐形眼镜继续冲洗；如刺激持续，就医； P273：避免释放到环境中。

光华化工
GUANGHUA CHEMICAL

2.6 其他危害：弱阴离子型乳液；避免和强氧化剂接触；不含磷、不含 ODS 消耗臭氧层物质，符合 RoHS、Weee 指令。

3 成分 / 组成信息

☑混合物 □纯品

组分名称	CAS 号	质量分数
聚醚与二甲基硅氧烷反应产物	商业保密	<20%
甲基丙烯酸	79-41-4	<2%
去离子水	7732-18-5	>40%

备注：功能性组分为商业机密，仅提供浓度区间；无《危险化学品目录》列明高浓度危险组分；最终腐蚀性以第三方危险特性鉴别报告为准。

4 急救措施

4.1 吸入：转移至空气新鲜处；吸入气雾引发呼吸道不适，症状持续则就医。

4.2 皮肤接触：立刻脱去全部受污染衣物，流动清水冲洗皮肤至少 10 分钟；出现皮肤刺激，就医。

4.3 眼睛接触：立即翻开眼睑，流动清水或者生理盐水持续冲洗不少于 15 分钟；刺激持续不退，就医。

4.4 食入：饮用足量温水，**严禁催吐**，不要自行诱导呕吐，立即就医。

4.5 给医生提示：本品乳液体系，可造成皮肤、眼部刺激；对症处理，无特异性解毒剂。

5 消防措施

5.1 合适灭火剂：雾状水、干粉、二氧化碳、砂土。

5.2 禁止灭火剂：无特殊禁忌。

5.3 燃烧有害分解产物：高温分解产生一氧化碳、二氧化硅烟气、有机分解产物。

5.4 消防员防护建议：佩戴自给式呼吸器 SCBA、全套消防防护服，在上风向灭火；尽可能将容器转移至空旷区域；用水冷却火场容器；容器变色、泄压发声，人员立即撤离。

6 泄漏应急处理

光华化工
GUANGHUA CHEMICAL

6.1 人员防护：疏散无关人员；处置人员穿戴耐化学品防护服、耐化学品手套、护目镜；避免皮肤眼睛直接接触泄漏乳液，防止地面打滑。

6.2 环境保护：严禁泄漏物流入下水道、雨水管网、河道；收集废液送入厂区废水处理系统预处理。

6.3 小量泄漏：砂土、惰性吸附材料吸附残液；收集进密闭容器，送入厂区废水处理系统。

6.4 大量泄漏：构筑围堤收容；物料泵入专用收集容器，交由具备资质危废处置单位处置。



7 操作处置与储存

7.1 操作注意事项

1）密闭操作，车间加强通风；操作人员经过岗位培训，遵守作业规程。

2）避免皮肤、眼睛直接接触，佩戴全套个人防护用品；地面注意防滑。

3）远离热源，工作场所禁止吸烟。

4）避免与强氧化剂混配接触。

5）使用前产品适度搅拌；切勿超量添加；轻装轻卸，防止包装桶破损泄漏；现场配备泄漏应急物资与消防器材。

7.2 储存条件

1）储存于阴凉通风库房，环境温度 5- 35℃；防冻，避免暴晒；保持容器密封完好。

2）与氧化剂、食品化学品分开存放，严禁混储。

3）按照消防法规、危化品仓储管理要求保管。

8 接触控制 / 个体防护

8.1 职业接触限值：混合物无国家规定职业接触限值。

8.2 工程控制：生产岗位加强通风，减少气雾产生。

8.3 呼吸防护：正常工况不需要；产生大量气雾时佩戴合适的防雾滴口罩。

8.4 手部防护：耐化学橡胶防护手套。

8.5 眼睛防护：佩戴护目镜（防冲击化学品防护眼镜）。

8.6 身体防护：耐化学品工作服。

9 理化特性

外观：白色乳状液体

气味：微弱特征气味

离子型：弱阴离子型

粘度（25℃）：1000- 3000 cs

pH 值：6.0- 8.0（原液）

相对密度（15℃）：1.00±0.05 g/cm³

闪点：无闪点（不燃液体）

溶解性：可在水中分散乳化

燃烧性：不燃

使用工艺：常温使用；原液直接添加或者用水稀释后投加；推荐添加量 0.1%- 0.3%；使用前适度搅拌。

备注：理化参数来源本产品 CMA- COA 第三方检测报告。

10 稳定性和反应性

10.1 稳定性：常温常压储存条件下稳定；防冻，冻结后会破坏乳液体系。

10.2 应避免接触物质：强氧化剂。

10.3 危险反应：和强氧化剂接触可发生化学反应。

10.4 危险分解产物：高温不完全燃烧产生二氧化硅烟气、一氧化碳、有机分解物；常温储存无分解。

11 毒理学信息

11.1 急性毒性：该混合物无高急性毒性数据。

11.2 皮肤腐蚀 / 刺激：类别 2，反复长期接触可引发皮肤发红、红斑。

11.3 眼损伤 / 眼刺激：类别 2A，可造成眼部刺激。

11.4 致敏性：无明确致敏记录。

11.5 致突变、致癌、生殖毒性：混合物组分未见明确致癌致突变证据。

12 生态学信息

12.1 水生毒性：对水生生物有害，具有长期持续毒性；原液严禁直接排放水体。

12.2 生物降解性：部分组分降解有限。 12.3 生物蓄积潜力：无显著生物蓄积。

12.4 其它生态效应：废水必须预处理达标之后排放。

光华化工
GUANGHUA CHEMICAL

13 废弃处置

13.1 化学品残余物：原液不可直接排放；厂区废水站预处理，或者委托具备资质危废处置单位处置。

13.2 污染包装容器：容器充分清洗后回收利用；残留废液按照危险废物管理。

13.3 提示：处置全过程遵守国家、地方环境保护、危废管理法规。

14 运输信息

14.1 UN 编号：不属于危险货物，无 UN 编号。

14.2 运输危险类别：非危险化学品。

14.3 包装类别：无。

14.4 包装方式：25kg、50kg 塑料大口吨桶包装。

14.5 运输注意事项：运输前检查包装密封完好；防冻、防止暴晒；禁止和强氧化剂、食品类货物混运；防止容器发生泄漏；防止倾倒泄漏造成路面打滑。

15 法规信息

本 SDS 编制参考法规：GB/T16483- 2008、GB/T17519- 2013、GB30000 系列 GHS 分类；《安全生产法》、《危险化学品安全管理条例》、RoHS、Weee 环保指令、地方环保安全生产相关规定。

说明：本产品不属于《危险化学品目录》列明的危险化学品。

16 其他信息

16.1 参考文献：本产品 CMA- COA 检测报告，企业 TDS 技术数据表。

16.2 修订说明：V2.0，按照 GB/T16483- 2008 现行国标编制；完整录入产品工艺使用参数。

16.3 编制部门：昆山光华化工材料有限公司- 技术工程部。

16.4 免责声明：本 SDS 依据现有测试、文献资料编制，仅供安全操作参考；使用者结合现场工况，自行评估使用安全风险。

光华化工
GUANGHUA CHEMICAL

Safety Data Sheet (SDS)

Product: Hot-Dip Galvanizing Defoamer (ZY-9174)

Prepared in accordance with: GB/T 16483-2008, GB/T 17519-2013, GB 30000 series GHS classification standards

SECTION 1: IDENTIFICATION

1.1 Product identifier: Hot-Dip Galvanizing Defoamer (ZY-9174)

1.2 Synonym: Polyether-dimethylsiloxane modified emulsion-type antifoaming and foam-suppressing agent

1.3 Recommended use: This product is a water-soluble high-efficiency antifoaming and foam-suppressing agent with dual functions of fast defoaming and long-term foam inhibition. It can work stably under high-temperature, strong acid-base and high-shear-force working conditions. Applicable for industrial cleaning fluids, coatings, adhesives and hot-dip-galvanizing related water-treatment systems. It can be added neat or after dilution with water; recommended dosage: 0.1%-0.3%. Agitate moderately before use.

1.4 Restrictions on use: Must not be used for food, pharmaceutical or potable-water systems.

1.5 Manufacturer: Kunshan Guanghua Chemical Materials Co., Ltd.

1.6 Address: No.341 Hubin North Road, Bacheng Town, Kunshan City, Jiangsu Province, P.R.China

光华化工
GUANGHUA CHEMICAL

1.7 Telephone: +86-13584927325

1.8 24-hour domestic emergency telephone (China): +86-13584927325

1.9 Prepared by: Engineering Department

1.10 Date of preparation: 2026-08-20

1.11 Revision: V2.0

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 GHS Hazard Classification: Skin Irritation Category 2; Eye Irritation Category 2A; Hazardous to aquatic life with long-lasting effects; Non-flammable liquid, no explosion hazard.

2.2 GHS Pictogram: Exclamation mark ⚠ GHS07

2.3 Signal word: Warning

2.4 Hazard Statements:

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

2.5 Precautionary Statements:

P280: Wear protective gloves and eye-protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

光华化工
GUANGHUA CHEMICAL

P273: Avoid release to the environment.

2.6 Other hazards: Weak-anionic emulsion. Avoid contact with strong oxidizing agents. Contains no phosphorus and no ozone-depleting substances (ODS). Complies with RoHS and Weee directives.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

☑ Mixture ☐ Substance

Chemical name	CAS-No.	Mass fraction
Reaction product of polyether and dimethylsiloxane	Trade secret	<20 %
Methacrylic acid	79-41-4	<2 %
De-ionized water	7732-18-5	>40 %

Remarks: Key functional components are treated as trade secrets; only concentration ranges are provided. No high-concentration hazardous ingredients listed in China Catalogue of Hazardous Chemicals. Final corrosive property shall be subject to third-party hazard identification test report.

SECTION 4: FIRST-AID MEASURES

4.1 Inhalation: Remove victim to fresh air. Seek medical attention if respiratory discomfort caused by mist inhalation persists.

4.2 Skin contact: Immediately remove all contaminated clothing. Rinse skin thoroughly with running water for at least 10 minutes. Seek medical help if skin irritation occurs.

光华化工
GUANGHUA CHEMICAL

4.3 Eye contact: Immediately hold eyelids apart, continuously flush eyes with plenty of running water or normal saline for not less than 15 minutes. Seek medical care if irritation persists.

4.4 Ingestion: Give sufficient warm water to drink. **Do NOT induce vomiting**. Call a physician immediately.

4.5 Notes to physician: This is an emulsion-type product, which may cause skin and eye irritation. Treat symptomatically; no specific antidote is available.



SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media: Water spray, dry chemical powder, carbon dioxide, sand.

5.2 Unsuitable extinguishing media: None known.

5.3 Hazardous decomposition products under fire conditions: Carbon monoxide, silica-containing fumes and organic decomposition substances generated upon high-temperature decomposition.

5.4 Advice for fire-fighters: Wear self-contained breathing apparatus (SCBA) and full protective turnout gear. Fight fire from up-wind direction. If safe to do so, move intact containers to open area. Cool exposed containers with water spray. Immediately evacuate personnel if containers discolor or venting noise occurs.

SECTION 6: ACCIDENTAL RELEASE MEASURES

光华化工
GUANGHUA CHEMICAL

6.1 Personal precautions: Evacuate non-essential personnel. Responders shall wear chemical-resistant protective clothing, chemical-resistant gloves and safety goggles. Avoid direct skin-eye contact with spilled emulsion; take anti-slip precautions.

6.2 Environmental precautions: Prevent spillage from entering sewers, storm drains and watercourses. Collect waste liquid and send to on-site wastewater pretreatment facility.

6.3 Small spill: Absorb residual liquid with sand or other inert absorbents. Collect waste in sealed containers and deliver to on-site wastewater treatment facility.

6.4 Large spill: Dike for containment. Pump liquid into dedicated collecting receptacles and hand over to licensed hazardous-waste disposal contractor.

SECTION 7: HANDLING AND STORAGE



7.1 Handling precautions

1) Operate in closed-system with adequate workshop ventilation. Operators shall receive position-specific training and follow operating procedures.

2) Avoid direct skin-eye contact. Wear complete set of personal protective equipment. Take anti-slip precautions for floor surfaces.

3) Keep away from heat sources. No smoking in working zone.

4) Avoid mixing-contact with strong oxidizing agents.

5) Agitate product moderately before use; avoid over-dosage. Handle drums

carefully to prevent rupture-leakage. Keep spill-response kits and fire-fighting equipment readily available.

7.2 Storage conditions

1) Store in cool and well-ventilated warehouse; ambient storage temperature: 5-35 °C. Protect from freezing and direct sunlight. Keep containers tightly sealed. Freezing will destroy the emulsion system.

2) Segregate strictly from oxidizing agents and food-grade commodities; no mixed-storage.

3) Store in compliance with fire-protection regulations and hazardous-chemical warehousing requirements.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Occupational exposure limits: No national occupational exposure limits established for this mixture.

8.2 Engineering controls: Provide sufficient ventilation at work stations to reduce mist generation.

8.3 Respiratory protection: Normally not required. Wear suitable mist-filter respirator when large amount of mist/aerosol is generated.

8.4 Hand protection: Chemical-resistant rubber protective gloves.

8.5 Eye protection: Impact-resistant chemical-safety goggles.

8.6 Body protection: Chemical-resistant work clothing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Milky-white liquid

Odor: Faint characteristic odor

Ionic type: Weak-anionic

Viscosity (25 °C): 1000-3000 cs

pH value: 6.0-8.0 (as-received liquid)

Relative density (15 °C): 1.00 ± 0.05 g/cm³

Flash point: Non-flammable, no measurable flash-point

Solubility: Dispersible and emulsifiable in water

Flammability: Non-combustible

Application notes: Operate at ambient temperature; use neat or dilute with water before dosing; recommended dosage 0.1%-0.3%; agitate moderately prior to use.

> Source of physical-chemical data: Third-party CMA-COA test report of this product.

SECTION 10: STABILITY AND REACTIVITY

10.1 Chemical stability: Stable under normal ambient temperature and pressure. Freezing condition will destroy emulsion system.

10.2 Incompatible materials: Strong oxidizing agents.

10.3 Hazardous reactions: Chemical reaction may occur upon contact with

光华化工
GUANGHUA CHEMICAL

strong oxidizing agents.

10.4 Hazardous decomposition products: Silica-containing fumes, carbon monoxide and organic decomposition products generated under incomplete high-temperature combustion; no decomposition under ambient storage.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Acute toxicity: No high acute-toxicity data available for this mixture.

11.2 Skin corrosion / irritation: Category 2; repeated or prolonged contact may cause skin redness and erythema.

11.3 Eye damage / eye irritation: Category 2A; may cause eye irritation.

11.4 Skin sensitization: No confirmed sensitizing-reaction records.

11.5 Germ-cell mutagenicity, carcinogenicity, reproductive toxicity: No clear evidence of carcinogenic or mutagenic hazards for mixture components.

SECTION 12: ECOLOGICAL INFORMATION (Non-mandatory under OSHA-HCS)

12.1 Aquatic toxicity: Harmful to aquatic life with long-lasting toxic effects. Raw product must not discharge directly to water bodies.

12.2 Biodegradability: Partial components have limited biodegradability.

12.3 Bioaccumulative potential: No significant bioaccumulation.

12.4 Other adverse environmental effects: Wastewater must be pre-treated before discharge.

光华化工
GUANGHUA CHEMICAL

SECTION 13: DISPOSAL CONSIDERATIONS (Non-mandatory under OSHA-HCS)

13.1 Product residues: Do not discharge untreated. Pretreat via on-site waste-water system or consign to licensed hazardous-waste disposal contractor.

13.2 Contaminated packaging containers: Thoroughly rinse containers for potential recycling. Residual waste liquid shall be managed as hazardous waste material.

13.3 Note: All disposal activities shall comply with national and local environmental-protection and hazardous-waste regulations.

SECTION 14: TRANSPORT INFORMATION (Non-mandatory under OSHA-HCS)

14.1 UN number: Not classified as dangerous goods, no UN-number assigned.

14.2 DOT hazard class: Non-hazardous commodity for transport.

14.3 Packing group: Not applicable.

14.4 Packaging: 25 kg, 50 kg plastic open-top IBC drums.

14.5 Transport advice: Inspect container tightness before shipment. Protect from freezing and direct sunlight. Do not co-transport with strong oxidants or food-stuff cargo. Prevent container leakage; prevent slip hazard caused by spilled liquid.

SECTION 15: REGULATORY INFORMATION (Non-mandatory under OSHA-HCS)

References for SDS compilation:

GB/T16483-2008, GB/T17519-2013, GB 30000 series GHS standards;

Work Safety Production Law, Regulations on Safety Management of Hazardous Chemicals, RoHS, Weee directives, local environmental-protection & work-safety provisions.

Note: This product is not listed in China Catalogue of Hazardous Chemicals.

SECTION 16: OTHER INFORMATION

16.1 References: CMA-COA test report of this product, enterprise TDS technical data sheet.

16.2 Revision note: Version V2.0. Compiled under current GB/T16483-2008 national standard; complete product application-process parameters are documented.

16.3 Prepared by: Engineering Department, Kunshan Guanghua Chemical Materials Co., Ltd.

16.4 Disclaimer: This SDS is compiled on the basis of available test data and literatures for safety-operation reference only. End-users shall independently assess safety risks according to actual on-site working conditions.